


AIRBRUSH CAMO-MASK





User Guide



Select suitable Airbrush
Camo-Mask for the model.
Spray the first camouflage color on model. In order to make the spraying procedure smoothly, suggest using Airbrush Camo-Mask marked with asterisk () to be the first camouflage color.



Suggest using Mask marked with asterisk (★) inside the Airbrush Camo-Mask to be the first Mask adhere on model. Position lines have been marked on the Mask which can help to fix the position.



Please follow the color guide to complete the procedure of using the Airbrush Camo-Mask.



Use scissor or cutter to cut the Airbrush Camo-Mask if it cannot be adhere on the unflatten area of model. Then, use tape or liquid mask fill up the gap.



The liquid mask can be used to fill up the gap between the first and second color of Airbrush Camo-Mask.



Adhere the Airbrush Camo-Mask on wheels after spraying the outer ring of wheels in black color, Then, spray the color on wheel, (If this Mask is included in the kit),



Remove all the Airbrush Camo-Mask after spraying the last camouflage color on model.



Spot-Pattern Masking Paper can be used for spraying the spot pattern (if Spot-Pattern Masking Paper is included in the kit)

Please visit our website
www.jsworkmodel.com

14+ Kit suitable for ages 14 to adult.

MADE IN CHINA

