

The Aviation Workshop is a dedicated group of modellers from around the world that have jointed together to bring you some of the finest decals, accessories, kits, etched sets and books available.



Model Alliance Decals - UK & The Aviation Workshop are trading names of The Aviation Workshop Publications Ltd & Gary Madgwick.

The On-Target Publications, AIRframe Journal & Airfix Magazine for Aircraft Modellers are all names registered to The Aviation Workshop Publications Ltd and may not be used without the permission in writing of the The Aviation Workshop Publications Ltd.

Decals Instructions:

These decals are a high quality product produced for The Aviation Workshop by Colourslide. The decals are very thin but very strong and flexible.

- Before painting the model, clean with Model Alliance 'Model Wipes'. This cleans the grease and any dust from the surface.
- The Surrace.

 2. We recommend that you wear Model Alliance 'Model Gloves' to handle the model whilst preparing it for painting.
- 3. For best results, spray the model with a Light Grey primer, any defects can then be made good.
- 4. For demarcation and camouflage lines, we recommend that you use Model Alliance 'Masking Film'.
- If you wish to use a decal fixing and finishing system, we recommend you use the Microscale System, do not use strong decals solvents such as Solvaset.
- 6 Once you are happy with the painting of the model, coat it in a clear gloss finish, this can either be over the entire model if the model is finished glossy or spot gloss finish in the area's that have a decal. A good clear surface finish should then be applied.
- 7. Cut each decal from the sheet as needed. Do not trim the clear varnish finish to close to the decal. Submerge the decal in warm water for about 10 seconds and remove to a flat surface and wait for the decal to release from the backing sheet. A small amount of washing up liquid in the warm water helps the decal release from the sheet.
- 8. These decals do not require a decal setting solution to lay flat or to conform to the model contours.
- With a pair of tweezers to hold the backing sheet, slide the decal in position on the model using a small soft brush. Do not use an old painting brush as bits can get under the decal.
- 10. Carefully remove any excess water with a soft cloth or tissue once you are happy with the position of the decal. Should you make a mistake, dip a brush in the warm water and ease under the edge of the decal. The decal will then easily move to the correct position and again remove the excess water.
- 11. When the decals are completely dry, gently wipe off all excess decal adhesive.
- 12. Leave the model to dry completely, spray or paint over the decals with a further clear finishing coat to your prefered finish.
- 13. Should the decal silver for any reason, this is because small air bubbles are under the decal. If found, prick with a pin and apply a small drop of Micro Sol to the decal and allow to dry for up to 12 hours.
- 14. Finally, coat the model with the required finish, either gloss, semi gloss or matt.
- 15. Decals are best stored flat and in a cool, dry place and should not be stored in direct sunlight, hot or humid conditions.
- 16. Should you have any problems with these decals please contact us at the address below.







To be used in conjunction with On-Target Special No.1
Op Telic Book

The Aviation Workshop

13 Charlton Road, Wantage,
Oxon, OXI2 8EP, UK

www.theaviationworkshop.co.uk
Email: aviation-workshop@btconnect.com