
Aussie Decals

P.O. Box 94 Redbank, QLD. 4301, Australia.



### MODELLERS NOTES

The first Seahawk known for blockade duties in the Gulf of Oman was 873 "Hussein's Harrassers" in November 1990, and was deployed on the HMAS Sydney. This aircraft was the first Australian aircraft into Kuwait after the ceasefire. There are two panels supplied: the coloured one was made on the return journey to Australia. This was painted on the Port side panel. From May to July 1991, 878 was deployed on HMAS Darwin for mine clearance and patrol duties. This aircraft had a black Tiger head with Arabic above it. The background must be painted on first with FS 36495 using the mask template supplied.

At the end of 1991, 873 was again deployed on HMAS Sydney in the North Red Sea for blockade duties. This time "Bad to the Bone" was painted on the Port side panel. Variations can be made with both these panels. 883 had "Hussein's Harrassers" on the Port side panel for most of 1992. 884 had the Arabic Tiger on the Starboard side panel for some time in 1993.

As at April 1993, all the above panels were painted over in Grey FS 36320.

For the side number, the '8' is always deleted; e.g. 873 = 73.

### NOTE

Fill Sonar Buoy panel before applying Decal

### **COLOUR NOTES**

Main Surface Colour: FS 36320 / Gunze Sangyo H307 / Modelmaster 1741 FS 35237 / Gunze Sangyo H337 / Modelmaster 1721 Under Surface Colour: FS 36495 / Gunze Sangyo H338 / Modelmaster 1732 FS 36495 / Gunze Sangyo H338 / Modelmaster 1732 FS 36320 / Gunze Sangyo H307 / Modelmaster 1741 FS 36320 / Gunze Sangyo H307 / Modelmaster 1741 Rotor Colour: Hub Colour:

Some Tail Rotors have been seen painted Matt Black.

## RECOMMENDED KITS

1/72 Scale: Hasegawa 1/48 Scale: Revell

Conversion Kit: FM Models, P.O. Box 1181 Springwood, Old. 4127

### **DECAL APPLICATION**

Cut around the required design
Soak in luke-warm water for 3 - 4 seconds

3. Stand the Decal on facial tissue

4. Moisten application area with plenty of water 5. Apply Decal by carefully sliding off backing paper

6. Use Decal setting agent to nestle Decal around body detail

7. Paint model with clear lacquer to hide Decal film


N.B. Decals adhere best to gloss surfaces.

This Decal film is very thin and will need extra care in application

## REFERENCE

APMA Magazines - Autumn, Winter, Spring, Summer 1992

We would like to thank Alex Wright, APMA and Tony Dwyer for their help in producing this sheet.



# 7373







5-708-2 N24-004 S-708-2 N24-004 73

7878



\$7082 N24-009


N24-009

7日

1234567890

## 12345 67890 12345 67890 • 7

1234567890



S-70B-2 N24-013 N24-014 N24-005 N24-001 N24-006 N24-002 N24-003 S-70B-2 S-70B-2 S-70B-2 S-70B-2 N24-013 N24-005 N24-006 N24-014 N24-001 N24-002 N24-003 S-70R-2 S-70B-2 S-70B-2 N24-011 N24-012 N24-015 N24-016 N24-008 N24-007 N24-010 S-70B-2 S-708-2 5-708-2 S-70B-2 S-70B-2 S-70B-2 S-70B-2 N24-011 N24-012 N24-015 N24-016 N24-008 N24-007 N24-010